

Seal and Shelter Product Application Chart

		Compression Foam Dock Seals					Frame Truck/Rail Dock Shelters				
		TS-101 Fixed Head	TS-103 Curtain Head	TS-500 Adj. Head	TS-101L Fixed L Pad	TS-103L Curtain L Pad	TC-400 Rigid	TC-300 Flex. Steel	TC-500 Flex. Wood	TC-900 Soft Sided	RC-200 Inflatable
Building and Door Dimensions	Door Width 8'-0" or less	●	●	■	●	●					
	Door Width 8'-0" to 9'-0"	●	●	■	●	●	■	●	■	●	●
	Door Width 9'-0" or greater				●	●	■	●	■	●	●
	Door Height 9'-0" or less (or 13'-0" or less off grade)*	●			●						
	Door Height 9'-0" or greater (or 13'-0" or more off grade)*		●	■		●	■	●	■	●	●
	Projecting Platform						■	●	■		●
	Free Standing Dock Leveler						■	●	■	●	
Drive Approach to Dock	Incline or Decline	● with tapered side pads	● with tapered side pads	■ with tapered side pads	● with tapered side pads	● with tapered side pads	■ with tapered sides	● with tapered sides	■ with tapered sides	● with tapered sides	
Trucks and Trailers Serviced	Only 8'-0" Wide or 8'-6" Wide	●	●	■	●	●	■	●	■	●	
	Widely Varying Sizes						■	●	■	●	
	Hydraulic Tailgates						■	●	■	●	
	Rear Step Section						■	●	■	●	
	Railroad Cars										●
Customer Needs	Full Width Access				●	●	■	●	■	●	●
	Traffic Volume** Heavy	● with 4" wear pleats	● with 4" wear pleats	■ with 4" wear pleats	● with 4" wear pleats	● with 4" wear pleats	■	●		●	●
	Medium	● with 8" wear pleats	● with 8" wear pleats	■ with 8" wear pleats	● with 8" wear pleats	● with 8" wear pleats	■	●		●	●
	Light	●	●	■	●	●	■	●	■	●	●
	Sealing: Excellent	●			●					●	
	Very Good		●			●					●
	Good			■			■	●	■		
Use with: Yard Jockey's***	● with add'l bumper proj.	● with add'l bumper proj.	■ with add'l bumper proj.	● with add'l bumper proj.	● with add'l bumper proj.	■	●	■	●		
Truck Leveler						■	●	■	●		

* 13'-0" is 4'-0" standard dock height plus the door height

*** Heavy: Over 6 trailers per door per shift Medium: 4 to 6 Light: 1 to 3

**** Also called switch or spotting tractors



Corporate Office

W194 N11481 McCormick Dr. • P. O. Box 309 • Germantown, WI 53022 • Phone: 1.800.624.8473 • Fax: 262.255.4199 • www.DockSystemsInc.com